

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : RENLEASE® QZ 5111

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Use in binder and release agents

Recommended restrictions on use : For industrial use only.

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium

Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : Berlin: 0049 30 19 24 0 & 0049 30 30 68 6 7 11
Bonn: 0049 228 19 27 0 & 0049 228 28 7 3 32 11
Erfurt: 0049 361 73 07 30
Freiburg: 0049 761 16 24 0
Göttingen: 0049 51 19 24 0 & 0049 551 38 31 80
Homburg: 0049 6841 19 24 0
Mainz: 0049 6131 19 24 0 & 0049 6131 23 24 66
München: 0049 89 19 24 0
Nürnberg: 0049 911 39 8 2 45 1
EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2

H225: Highly flammable liquid and vapour.

RENLEASE® QZ 5111





Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

| | |
|--|--|
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |
| Aspiration hazard, Category 1 | H304: May be fatal if swallowed and enters airways. |
| Long-term (chronic) aquatic hazard, Category 2 | H411: Toxic to aquatic life with long lasting effects. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

| | | |
|--------------------------|---|---|
| Hazard pictograms | : |     |
| Signal word | : | Danger |
| Hazard statements | : | H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. |
| Precautionary statements | : | Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P273 Avoid release to the environment. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 Do NOT induce vomiting. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P391 Collect spillage. |

Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrotreated light

Methylcyclohexane

octane

hexane (containing < 5 % n-hexane (203-777-6))

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|--|---|--|--------------------------|
| Naphtha (petroleum), hydrotreated light | 64742-49-0 265-151-9 01-2119475133-43 | Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 | >= 70 - < 90 |
| octane | 111-65-9 203-892-1 601-009-00-8 01-2119463939-19 | Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 | >= 2,5 - < 10 |
| Methylcyclohexane | 108-87-2 203-624-3 01-2119556887-18 | Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 M-Factor (Acute aquatic toxicity): 1 | >= 2,5 - < 10 |
| hexane (containing < 5 % n-hexane (203-777-6)) | 107-83-5 203-523-4 601-007-00-7 01-2120768140-61 | Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 Flam. Liq. 2; H225 | >= 2,5 - < 10 |
| cyclohexane | 110-82-7 203-806-2 601-017-00-1 01-2119463273-41 | Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute | >= 2,5 - < 10 |

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

| | | | |
|--|--|---|--|
| | | aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 | |
|--|--|---|--|

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Treat symptomatically.
Get medical attention if symptoms occur.
- If inhaled : Consult a physician after significant exposure.
If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.12.2017 |
| 2.0 | 06.02.2020 | 400001008255 | Date of first issue: 08.12.2017 |

Print Date 10.02.2020

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Specific extinguishing methods : No data is available on the product itself.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Refer to protective measures listed in sections 7 and 8.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

- For disposal considerations see section 13., See Section 1 for emergency contact information.,
For personal protection see section 8.

RENLEASE® QZ 5111

Version Revision Date: SDS Number: Date of last issue: 12.12.2017
2.0 06.02.2020 400001008255 Date of first issue: 08.12.2017

Print Date 10.02.2020

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Container may be opened only under exhaust ventilation hood.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Keep in properly labelled containers.
- Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.
- Storage class (TRGS 510) : 3, Flammable liquids
- Recommended storage temperature : 2 - 40 °C
- Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

- Specific use(s) : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version
2.0

Revision Date:
06.02.2020

SDS Number:
400001008255

Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---|---|-------------------------------|------------------------------------|----------------|
| Methylcyclohexane | 108-87-2 | AGW | 200 ppm 810 mg/m ³ | DE TRGS 900 |
| Peak-limit: excursion factor (category) | 2;(II) | | | |
| Further information | Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). | | | |
| octane | 111-65-9 | AGW | 500 ppm 2 400 mg/m ³ | DE TRGS 900 |
| Peak-limit: excursion factor (category) | 2;(II) | | | |
| Further information | Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). | | | |
| Ethene, homopolymer | 9002-88-4 | AGW (Inhalable fraction) | 10 mg/m ³ | DE TRGS 900 |
| Peak-limit: excursion factor (category) | 2;(II) | | | |
| Further information | General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). | | | |
| | | AGW (Alveolate fraction) | 1,25 mg/m ³ | DE TRGS 900 |
| Peak-limit: excursion factor (category) | 2;(II) | | | |
| Further information | General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). | | | |
| cyclohexane | 110-82-7 | TWA | 200 ppm 700 mg/m ³ | 2006/15/EC |
| Further information | Indicative | | | |
| | | AGW | 200 ppm 700 mg/m ³ | DE TRGS 900 |
| Peak-limit: excursion factor (category) | 4;(II) | | | |
| Further information | Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible) | | | |
| hexane (containing | 107-83-5 | AGW | 500 ppm | DE TRGS |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
 Date of first issue: 08.12.2017

Print Date 10.02.2020

| | | | |
|---|--|-------------|-----|
| < 5 % n-hexane (203-777-6)) | | 1 800 mg/m3 | 900 |
| Peak-limit: excursion factor (category) | 2;(II) | | |
| Further information | Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). | | |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|-------------------|-----------|-----------------|----------------------------|------------------|
| Methylcyclohexane | Workers | Inhalation | Long-term systemic effects | 64,3 mg/m3 |
| | Workers | Inhalation | Acute systemic effects | 1354,6 mg/m3 |
| | Workers | Dermal | Long-term systemic effects | 1,7 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 16 mg/m3 |
| | Consumers | Inhalation | Acute systemic effects | 1016 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 0,8 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 0,4 mg/kg bw/day |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|-------------------|---------------------------|-------------------------------|
| Methylcyclohexane | Fresh water | 1,34 µg/l |
| | Marine water | 0,134 µg/l |
| | Freshwater - intermittent | 13,4 µg/l |
| | Fresh water sediment | 0,036 mg/kg dry weight (d.w.) |
| | Marine sediment | 0,003 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 273 µg/l |
| | Soil | 0,01 mg/kg dry weight (d.w.) |

8.2 Exposure controls**Personal protective equipment**

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Emulsion

Colour : colourless

Odour : solvent-like

Odour Threshold : No data is available on the product itself.

pH : No data is available on the product itself.

Melting point/freezing point : No data available

Boiling point : 84 °C

Flash point : -8,99 °C
Method: Pensky-Martens closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Burning rate : No data is available on the product itself.

Upper explosion limit / Upper flammability limit : 7,7 %(V)

Lower explosion limit / Lower flammability limit : 0,6 %(V)

Vapour pressure : ca. 290 hPa (50 °C)

Relative vapour density : No data is available on the product itself.

Relative density : ca. 0,71 (20 °C)

Density : ca. 0,71 g/cm³ (20 °C)
Method: DIN 53217

Solubility(ies)
Water solubility : practically insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n- : No data is available on the product itself.

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

octanol/water

Auto-ignition temperature : 250 °C

Decomposition temperature : No data is available on the product itself.

Viscosity

Viscosity, dynamic : ca. 30 mPa.s
Method: ISO 3219

Viscosity, kinematic : 7 - 20 mm²/s (40 °C)

Flow time : 26 s
Cross section: 4 mm
Method: DIN 53211

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

9.2 Other information

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong acids
Strong oxidizing agents

10.6 Hazardous decomposition products

Carbon oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

Naphtha (petroleum), hydrotreated light:

Acute oral toxicity : LD50 (Rat, male and female): > 5 000 mg/kg
Method: OECD Test Guideline 401

octane:

Acute oral toxicity : LD50 (Rat, male and female): > 5 000 mg/kg
Method: OECD Test Guideline 401

Methylcyclohexane:

Acute oral toxicity : LD50 (Rabbit): 4 000 - 4 500 mg/kg

cyclohexane:

Acute oral toxicity : LD50 (Rat): 5 500 - 6 000 mg/kg

LD50 (Rat): 12 705 mg/kg

Method: No information available.

Components:

Naphtha (petroleum), hydrotreated light:

Acute inhalation toxicity : LC50 (Rat, male and female): > 7 630 mg/l
Exposure time: 4 h
Test atmosphere: vapour

octane:

Acute inhalation toxicity : LC50 (Rat, male and female): > 24,88 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Methylcyclohexane:

Acute inhalation toxicity : LC50 (Rat): > 26,3 mg/l
Exposure time: 1 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

cyclohexane:

Acute inhalation toxicity : LC50 (Rat, male and female): > 19 070 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

Components:

Naphtha (petroleum), hydrotreated light:

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

octane:

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Methylcyclohexane:

Acute dermal toxicity : LD50 (Rabbit): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Components:

Naphtha (petroleum), hydrotreated light:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Skin irritation

octane:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Skin irritation

Methylcyclohexane:

Species: Rabbit
Result: Skin irritation

hexane (containing < 5 % n-hexane (203-777-6)):

Assessment: Irritating to skin.

cyclohexane:

Result: Skin irritation

Serious eye damage/eye irritation

Components:

Naphtha (petroleum), hydrotreated light:

Species: Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.12.2017 |
| 2.0 | 06.02.2020 | 400001008255 | Date of first issue: 08.12.2017 |

Print Date 10.02.2020

Method: OECD Test Guideline 405

Result: No eye irritation

octane:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Methylcyclohexane:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Respiratory or skin sensitisation

Components:

Naphtha (petroleum), hydrotreated light:

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

octane:

Test Type: Maximisation Test

Exposure routes: Dermal

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

Methylcyclohexane:

Exposure routes: Skin

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

Assessment: No data available

Germ cell mutagenicity

Components:

Naphtha (petroleum), hydrotreated light:

Genotoxicity in vitro : Test Type: Ames test

Result: negative

: Test Type: In vitro mammalian cell gene mutation test

Result: negative

octane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: human lymphoblastoid cells

Concentration: 5% v/v

Metabolic activation: with and without metabolic activation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.12.2017 |
| 2.0 | 06.02.2020 | 400001008255 | Date of first issue: 08.12.2017 |

Print Date 10.02.2020

Method: OECD Test Guideline 476

Result: negative

: Test Type: Chromosome aberration test in vitro

Test system: rat hepatocytes

Concentration: 2.5, 5, 10µg/ml

Method: OECD Test Guideline 473

Result: negative

: Test Type: Ames test

Test system: Salmonella tryphimurium and E. coli

Concentration: 250µg/ml

Metabolic activation: with and without metabolic activation

Method: No information available.

Result: negative

Methylcyclohexane:

Genotoxicity in vitro

: Concentration: 8 - 100 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

: Concentration: 61.3 - 980 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

: Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Components:

Naphtha (petroleum), hydrotreated light:

Genotoxicity in vivo

: Test Type: Micronucleus test

Application Route: Inhalation

Result: negative

Test Type: In vivo micronucleus test

Test species: Rat

Application Route: Intraperitoneal injection

Result: negative

Germ cell mutagenicity-
Assessment

: No data available

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

Carcinogenicity

Components:

Naphtha (petroleum), hydrotreated light:

Species: Mouse, male

Application Route: Dermal

Result: negative

Carcinogenicity - Assessment : No data available

Reproductive toxicity

Components:

Naphtha (petroleum), hydrotreated light:

Effects on fertility

: Test Type: Two-generation study

Species: Rat, male and female

Application Route: inhalation (vapour)

General Toxicity - Parent: No observed adverse effect level:

$\geq 20\ 000\ \text{mg/m}^3$

General Toxicity F1: No observed adverse effect level: $\geq 20\ 000\ \text{mg/m}^3$

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

octane:

Test Type: Two-generation study

Species: Rat, male and female

Application Route: inhalation (vapour)

Dose: 0,900,3000,9000 parts per million

Duration of Single Treatment: 6 h

Frequency of Treatment: 5 days/week

General Toxicity - Parent: No observed adverse effect level:

$31\ 680\ \text{mg/m}^3$

General Toxicity F1: No observed adverse effect level: $10\ 560\ \text{mg/m}^3$

Method: OECD Test Guideline 416

Result: negative

Methylcyclohexane:

Species: Rat, male and female

Application Route: Oral

Dose: 250 milligram per kilogram

Method: OECD Test Guideline 422

Result: negative

Species: Rat, male and female

Application Route: Inhalation

Dose: $2020\ \text{mg/m}^3$

Method: OECD Test Guideline 416

Result: negative

Components:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.12.2017 |
| 2.0 | 06.02.2020 | 400001008255 | Date of first issue: 08.12.2017 |

Print Date 10.02.2020

Naphtha (petroleum), hydrotreated light:

Effects on foetal development : Species: Rat
Application Route: inhalation (vapour)
General Toxicity Maternal: No observed adverse effect level: 23 900 mg/m³
Teratogenicity: No observed adverse effect level: 23 900 mg/m³
Result: No adverse effects

octane:

Test Type: Embryo-foetal development
Species: Rabbit
Application Route: inhalation (vapour)
Dose: 0, 500, 2000, 7000 ppm
Duration of Single Treatment: 12 d
General Toxicity Maternal: No observed adverse effect concentration: > 7 000 ppm
Developmental Toxicity: No observed adverse effect concentration: > 7 000 ppm
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Dose: 0, 900, 3000, 9000 ppm
Duration of Single Treatment: 9 d
General Toxicity Maternal: No observed adverse effect level: 10 560 mg/m³
Developmental Toxicity: No observed adverse effect level: 31 680 mg/m³
Method: OECD Test Guideline 414
Result: No teratogenic effects

Methylcyclohexane:

Species: Rabbit
Application Route: Inhalation
General Toxicity Maternal: No observed adverse effect level: 28 100 mg/m³
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat
Application Route: Inhalation
General Toxicity Maternal: No observed adverse effect level: 1 720 mg/m³
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

STOT - single exposure

Components:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.12.2017 |
| 2.0 | 06.02.2020 | 400001008255 | Date of first issue: 08.12.2017 |

Print Date 10.02.2020

Naphtha (petroleum), hydrotreated light:
Exposure routes: inhalation (vapour)
Target Organs: Narcotic effects
Assessment: May cause drowsiness or dizziness.

octane:
Exposure routes: inhalation (vapour)
Target Organs: Central nervous system
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Methylcyclohexane:
Exposure routes: Inhalation
Target Organs: Respiratory Tract
Assessment: May cause drowsiness or dizziness.

hexane (containing < 5 % n-hexane (203-777-6)):
Assessment: May cause drowsiness or dizziness.

cyclohexane:
Exposure routes: Inhalation
Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

Naphtha (petroleum), hydrotreated light:
Species: Rat
NOEL: < 500
Application Route: Oral
Method: No information available.

Species: Rat
NOEL: > 2000
Application Route: Dermal
Method: No information available.

octane:
Species: Rat, male and female
NOAEL: 24,3 mg/l
Application Route: inhalation (vapour)
Test atmosphere: vapour
Exposure time: 13 weeks Number of exposures: 6h/d, 5d/wk
Dose: 668, 2220 and 6646ppm
Group: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.12.2017 |
| 2.0 | 06.02.2020 | 400001008255 | Date of first issue: 08.12.2017 |

Print Date 10.02.2020

Method: OECD Test Guideline 413

Remarks: Information given is based on data obtained from similar substances.

Species: Rat, male

NOAEL: 8,4 mg/l

Application Route: inhalation (vapour)

Test atmosphere: vapour

Exposure time: 13 weeks Number of exposures: 6h/d. 5d/wk

Dose: 1.9, 3.1, 8.4mg/L

Group: yes

Method: OECD Test Guideline 413

Remarks: Information given is based on data obtained from similar substances.

Species: Rat, male

NOAEL: > 14 mg/l

Application Route: inhalation (vapour)

Test atmosphere: vapour

Exposure time: 3 days Number of exposures: 8hr/d

Dose: 0, 1.4, 4.2, 14g/m³

Group: yes

Method: No information available.

Methylcyclohexane:

Species: Rat, male and female

NOAEL: 100 mg/kg

Application Route: Ingestion

Exposure time: 28 d Dose: 100, 300, 1000 mg/kg bw/day

Method: OECD Test Guideline 407

Species: Rat, male and female

NOAEL: 250 mg/kg

Application Route: Ingestion

Exposure time: 28 d Dose: 62.5, 250, 1000 mg/kg bw/da

Method: OECD Test Guideline 422

Species: Rat, male and female

NOEC: 250

Application Route: Ingestion

Test atmosphere: vapour

Exposure time: 8 640 h Number of exposures: 7 d

Method: Subacute toxicity

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

Components:

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

octane:

May be fatal if swallowed and enters airways.

Methylcyclohexane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.12.2017 |
| 2.0 | 06.02.2020 | 400001008255 | Date of first issue: 08.12.2017 |

Print Date 10.02.2020

May be fatal if swallowed and enters airways.

hexane (containing < 5 % n-hexane (203-777-6)):
May be fatal if swallowed and enters airways.

cyclohexane:
May be fatal if swallowed and enters airways.

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Naphtha (petroleum), hydrotreated light:

Toxicity to fish : LL50 : 10 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 4,5 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (algae)): 3,7 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201
- NOELR (Pseudokirchneriella subcapitata (algae)): 0,5 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 2,6 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211
- octane:
- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2,587 mg/l
Exposure time: 96 h
Method: QSAR
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,3 mg/l
Exposure time: 48 h
Test Type: static test
Method: Other guidelines
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (algae)): 2,084 mg/l
Exposure time: 72 h
Method: QSAR
- NOELR (Pseudokirchneriella subcapitata (algae)): 0,466 mg/l
Exposure time: 72 h
Method: QSAR
- M-Factor (Acute aquatic toxicity) : 1
- Toxicity to microorganisms : EL50 (Tetrahymena pyriformis): 10,86 mg/l
Exposure time: 48 h
Method: QSAR
- Toxicity to fish (Chronic toxicity) : 0,579 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)
Method: QSAR
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

NOEC: 0,17 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

Methylcyclohexane:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): 2,07 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,326 mg/l
Exposure time: 48 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (algae)): 0,134 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,0221 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : NOEC (activated sludge): 2,755 mg/l
Exposure time: 14 d
Test Type: static test
Test substance: Fresh water

hexane (containing < 5 % n-hexane (203-777-6)):

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

cyclohexane:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4,53 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203

LC50 : 93 - 117 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

LC0 : 32 mg/l
Exposure time: 96 h
Method: No information available.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,9 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

EC50 : 3,78 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : IC50 : > 500 mg/l
Exposure time: 72 h

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 4,425 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,925 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : IC50 : 24 mg/l
Exposure time: 15 h

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

Components:

Naphtha (petroleum), hydrotreated light:

Biodegradability : Result: Inherently biodegradable.

octane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %
Exposure time: 10 d

Methylcyclohexane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

Photodegradation : Test Type: Air
Rate constant: < .00001
Degradation (direct photolysis): 50 %

cyclohexane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: < 60 %
Exposure time: 28 d

12.3 Bioaccumulative potential

Components:

octane:

Bioaccumulation : Species: Other
Exposure time: 105 min
Temperature: 15 °C
Bioconcentration factor (BCF): 198,7

Partition coefficient: n-octanol/water : log Pow: 5,15

Methylcyclohexane:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Exposure time: 56 d
Bioconcentration factor (BCF): 95 - 321
Method: flow-through test

Partition coefficient: n-octanol/water : log Pow: 3,88

cyclohexane:

Bioaccumulation : Bioconcentration factor (BCF): 89

Partition coefficient: n-octanol/water : log Pow: 3,44

12.4 Mobility in soil

Components:

Naphtha (petroleum), hydrotreated light:

Distribution among environmental compartments : Koc: > 60,7 - < 229,2, log Koc: > 1,783 - < 2,36
Method: Calculation method

octane:

Distribution among environmental compartments : Koc: 436,8, log Koc: 2,64
Method: Calculation method

Methylcyclohexane:

Distribution among environmental compartments : Koc: 233,9

cyclohexane:

Distribution among : Koc: 160

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

environmental compartments

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

IATA

14.1 UN number : UN 1993
14.2 UN proper shipping name : Flammable liquid, n.o.s.

(NAPHTA, HYDROTREATED LIGHT AND HEXANE, MIXTURE OF ISOMERS (MAX. 5% N-HEXANE), Methylcyclohexane)

14.3 Transport hazard class(es) : 3

14.4 Packing group : II

Labels : Class 3 - Flammable liquids

Packing instruction (cargo aircraft) : 364

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

Packing instruction : 353
(passenger aircraft)

IMDG

14.1 UN number : UN 1993

14.2 UN proper shipping name : FLAMMABLE LIQUID, N.O.S.

(NAPHTA, HYDROTREATED LIGHT AND HEXANE, MIXTURE OF ISOMERS (MAX. 5% N-HEXANE), Methylcyclohexane)

14.3 Transport hazard class(es) : 3

14.4 Packing group : II

Labels : 3

EmS Code : F-E, S-E

14.5 Environmental hazards

Marine pollutant : yes

ADR

14.1 UN number : UN 1993

14.2 UN proper shipping name : FLAMMABLE LIQUID, N.O.S.

(NAPHTA, HYDROTREATED LIGHT AND HEXANE, MIXTURE OF ISOMERS (MAX. 5% N-HEXANE), Methylcyclohexane)

14.3 Transport hazard class(es) : 3

14.4 Packing group : II

Labels : 3

14.5 Environmental hazards

Environmentally hazardous : yes

RID

14.1 UN number : UN 1993

14.2 UN proper shipping name : FLAMMABLE LIQUID, N.O.S.

(NAPHTA, HYDROTREATED LIGHT AND HEXANE, MIXTURE OF ISOMERS (MAX. 5% N-HEXANE), Methylcyclohexane)

14.3 Transport hazard class(es) : 3

14.4 Packing group : II

Labels : 3

14.5 Environmental hazards

Environmentally hazardous : yes

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - List of substances subject to authorisation - Future sunset date : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

P5c

FLAMMABLE LIQUIDS

34

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water contaminating class (Germany) : WGK 3 highly hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : Total dust:
Not applicable
: Inorganic substances in powdered form:
Not applicable
: Inorganic substances in vapour or gaseous form:
Not applicable
: Organic Substances:
Not applicable
: Carcinogenic substances:
Not applicable
: Mutagenic:
Not applicable
: Toxic to reproduction:
Not applicable

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

RENLEASE® QZ 5111

Version 2.0 Revision Date: 06.02.2020 SDS Number: 400001008255 Date of last issue: 12.12.2017
Date of first issue: 08.12.2017

Print Date 10.02.2020

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOIC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H336 : May cause drowsiness or dizziness.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

RENLEASE® QZ 5111

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12.12.2017 |
| 2.0 | 06.02.2020 | 400001008255 | Date of first issue: 08.12.2017 |

Print Date 10.02.2020

| | |
|-------------------|---|
| Flam. Liq. | : Flammable liquids |
| Skin Irrit. | : Skin irritation |
| STOT SE | : Specific target organ toxicity - single exposure |
| 2006/15/EC | : Europe. Indicative occupational exposure limit values |
| DE TRGS 900 | : Germany. TRGS 900 - Occupational exposure limit values. |
| 2006/15/EC / TWA | : Limit Value - eight hours |
| DE TRGS 900 / AGW | : Time Weighted Average |

Further information

Classification of the mixture:

| | |
|-------------------|------|
| Flam. Liq. 2 | H225 |
| Skin Irrit. 2 | H315 |
| STOT SE 3 | H336 |
| Asp. Tox. 1 | H304 |
| Aquatic Chronic 2 | H411 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.