



**Backing:** Aluminum Foil  
**Adhesive:** Acrylic  
**Liner:** Paper  
**Colors:** Aluminum

**Standard Sizes:** 36" x 60Yd

### Applications

- Aircraft sealing and masking
- Window mask to protect aircraft canopies, windshields, and passenger window surfaces from crazing or hazing during paint stripping operations
- Heavy duty vapor barrier sealing for sheet metal flexible, and fiberglass duct systems
- Insulation seal, patch, and repair

### Features

- Heavy Duty Foil Backing
- Acrylic Adhesive
- Paper Release Liner

### Benefits

- Provides a barrier to air, moisture, and corrosion
- Acts as a heat shield to minimize heat transfer
- Conformable for irregular surfaces and contours
- Excellent bond to most surfaces
- Solvent resistant
- Excellent high temperature performance
- Perfect for die-cutting

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	5.5 mils	0.140 mm	ASTM D-1000
<b>Foil Thickness</b>	3.0 mils	0.328 mm	ASTM D-1000
<b>Adhesion to Steel</b>	50 oz/in	5.47 N/cm	PSTC-101
<b>Tensile Strength</b>	26 lb/in	45.53 N/cm	ASTM D-1000
<b>Operating Temperature</b>	0 to 260 °F	-17 to 127 °C	

Recommended Storage Conditions: 60-80 °F at 40-60% RH  
 Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a