


Premium High Temperature Splicing Tape



Backing: Treated Polyester Film

Adhesive: Silicone

Liner: Polyester Film

Colors: Blue

Specifications: N/A

Standard Sizes: 2" x 72Yd, 3" x 72Yd

Applications

- Splicing low-surface energy materials
- Splicing coated or uncoated papers or corrugate
- Foil splicing
- Tape splicing/manufacturing

Features

- Silicone Release-Treated PET Backing
- Silicone Adhesive
- Polyester Release Liner

Benefits

- Thin, low-profile film
- Excellent tensile strength and durability
- Blue for high visibility
- Outstanding adhesion to low-energy substrates
- Excellent shear strength for improved splice bond
- Performs well in extremely high temperatures
- Die-cutable

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.0 mils	0.076 mm	ASTM D-1000
Adhesion to Steel	35 oz/in	3.83 N/cm	PSTC-101
Adhesion to Backing	25 oz/in	2.74 N/cm	PSTC-101
Tensile Strength	25 lb/in	43.78 N/cm	ASTM D-1000
Max Performance Temp	400 °F	204 °C	
Elongation	125%		

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.